

# CUSTOM SANDBLASTED ADA SIGNS

## SAMPLE SPEC SHEET

### SECTION 10426 SIGNAGE AND GRAPHICS

#### PART 1 GENERAL

##### 1.01 SECTION INCLUDES

- A. Room signs

##### 1.02 SUBMITTALS

- A. Manufacturers must submit 3 references showing comparable products for projects completed within the last 5 years.
- B. Manufacturer's Data: Submit manufacturer's descriptive literature and specifications, including color samples of material for selection, as applicable for approval.
- C. Submit shop drawings listing sign styles, lettering and locations, and overall dimensions of each sign.
- D. Submit full size sample sign of type, style and color specified including method of attachment.

##### 1.03 SYSTEM DESCRIPTION

- A. Signage package shall meet the requirements of the Americans with Disabilities Act - 1990 Accessibility Guidelines for Buildings and Facilities and ANSI A117.1 - 1992.

#### PART 2 PRODUCTS

##### 2.01 MANUFACTURER - Signs

- A. Graphics 22 Signs, Inc. 5212 Lytle Street Pittsburgh, PA 15207  
Fax: 412.422.1226 Phone: 412.422.1125 email: sales@graphics22signs.com
- B. Signs shall have the following characteristics:
  - 1. Tactile characters/symbols shall be raised 1/32 inch from sign plate face [for ADA compliance].
  - 2. Signs shall be of one-piece construction; added-on and/or engraved characters are unacceptable.
  - 3. Text shall be accompanied by Grade 2 braille.
  - 4. All letters, numbers and/or symbols shall contrast with their background - either light characters on a dark background or dark characters on a light background. Characters and background shall have matte finish.

**CUSTOM DESIGN ADA SIGNS  
SAMPLE SPEC SHEET - page 2**

2.02 SIGNAGE

- A. Sign material shall consist of melamine, approximately 1/8" thick, with background painted a contrasting color.
- B. Lettering style shall be [name of typestyle], upper case.
- C. Sizes of letters and numbers shall be as follows:
  - 1. Room numbers shall be 5/8" high [or specify height].
  - 2. Lettering for room usage and directional identification shall be 5/8" high [or specify height].
  - 3. Lettering for restroom identification shall be 5/8" high, corresponding symbols shall be 3" high [or specify height].
- D. Letters and numbers shall be centered [or specify location] on sign.
- E. Grade 2 braille [for signs requiring braille] shall be placed directly below last line of letters or numbers [or specify location].
- F. Specify corner style.

2.03 SIGN SIZE

- A. Per Schedule

2.04 SIGN SCHEDULE

- A. Provide the following interior signs: [Provide complete list of required signs including text and symbols, if any. Indicate sizes and quantity of each.]

**CUSTOM DESIGN ADA SIGNS  
SAMPLE SPEC SHEET - page 3**

**PART 3 EXECUTION**

**3.01 EXAMINATION**

- A. Examine installation areas to insure that proper condition exist for timely completion of installation.

**3.02 PREPARATION**

- A. Verify that mounting locations and height for each sign will comply with ADA Accessibility Guidelines.
- B. Mounting locations should be smooth and free of all dirt, dust, grease, etc.

**3.03 INSTALLATION**

- A. Mount signs level and plumb using manufacturer's recommended standard mounting hardware of vinyl foam tape or holes and screws.
- B. Remove excess adhesives, etc. from exposed sign surfaces as recommended by adhesive manufacturer. Clean sign surfaces as needed.